
**elbaC Cable**

ZAC sous le Beer - RD 836
F-27730 BUEIL (Eure - France)
Tél : +33 (0)2 32 62 00 92
Fax : +33 (0)2 76 01 31 80
www.elbac.fr / info@elbac.fr

**Construction**

Inner conductor		① - ②		
Material	Annealed copper			
Diameter	Ø 0.78 mm			
Area	0.48 mm ²			
Insulation				
Material	HDPE			
Diameter	Ø 1.30 mm			
Assembly				
2 pairs				
Colors	See color table			
Lay length				
Mylar spiral	③			
Coverage	≥ 125%			
Drain wire			④	
Material	Tinned copper			
Diameter	Ø 0.45 ± 0.008 mm			
Screen			⑤	
Material	Alu/PET (40µ/12µ)			
Coverage	≥ 125 %			
Rip Cord	200D			⑥
Sheath			⑦	
Material	PVC Red Flame retardant IEC 332-1 (C2)			
Diameter	Ø 6.20 mm			
Mass	50 kg/km			
Marking of sheath				
Printing with XXX : Quantity in meter still available per reel DDDDD : Date code	SYT+/LY9ST 2P AWG20 - elbaC 305902 - DDDDD - XXX m			
Color / Process	Black / Ink jet			
Step	1 m			

Notes**Electrical characteristics**

Impedance	100 ± 20 Ω
Mutual paires capacitance	70 nF/km
Max conductor DC resistance	39 Ω/km
Propagation velocity ratio	65%
Rated voltage	200V
Insulation resistance 20°C	> 500MΩ.km

Performances

Frequency MHz	Max attenuation dB/100m	NEXT dB
0.001	0.200	70
0.040	0.350	66
0.150	0.850	57
0.300	1.300	53
1.000	2.500	45
2.000	3.500	40

Color table

Pairs	Colors		Lay Length (mm)
	A	B	
①	Light blue/White	White	20
②	Light blue/Dark blue	Dark blue	23

According to NF C93-529

Meet Standards

Fire performance :	EN 50575:2014/A1:2016
Environment :	European directive 2011/65/EU
Marking :	CE
Fire reaction :	IEC 60332-1 NF C 32-070 Classe C2

Thermal characteristics

CPR fire reaction class	E _{ca}
Rated temperature	-15 / 70°C

Mechanical characteristics

Static (d = sheath diameter)	r = 6 × d
Dynamic (d = sheath diameter)	r = 12 × d

Packaging

- B1 : 100m / Carton Box
- W5 : 500m / Wooden Drum